

| | | |
|----------------------------------|---|---|
| Capacity | 2.0Hp | 1.5Hp |
| Type | Wall-mounted, Split-type, Inverter | Wall-mounted, Split-type, Inverter |
| Refrigerant | R32 | R32 |
| Rated Cooling Capacity (Min-Max) | At least 18000 (5200-18500) Btu/h 5.28 (1.52-5.42) | At least 12300 (4100-13000) Btu/h 3.6 (1.2-3.81) |
| Energy Class | | |
| Power Consumption (kW) | 1.880 | 1.175 |
| COP (W/W) | 2.81 | 3.07 |
| CSPF (Wh/Wh) | 5.02 | 4.6 |
| Rated Running Current (A) | 8.25 | 5.28 |
| Energy Efficiency Ratio | 9.85 | 9.96 |
| Power Supply (V/Ph/Hz) | 220/1/60 | 220/1/60 |
| Airflow Rate (H/M/L/Q) | 430/380/290/260 | 400/330/250/200 |
| Sound Level (H/M/L/Q) | 42/39/33/30 | 39/33/26/21 |
| Min Circuit Amps (A) | 12.6 | 10.6 |
| Sound Level (Outdoor Unit) | 52 dBA | 48 dBA |
| Compressor | Hermetically Sealed Rotary Type | Hermetically Sealed Rotary Type |
| Key Features | Timer, Auto Swing, Fast Cooling, Silent Mode, Wireless Remote | Timer, Auto Swing, Fast Cooling, Silent Mode, Wireless Remote |

| At least 1.5hp Window Type Aircon Unit | Comply/Not Comply |
|---|-------------------|
| Key Features | |
| - EER Ratings: 11.2 (13.7-10.2) | |
| - Wattage: 2160 Watts (430-2650) | |
| - Full DC Inverter | |
| - Wifi Controlled | |
| - Multi Stage Air Filter | |
| - R32 Refrigerant | |
| - Soft Start Up and Quick cooling feature | |
| - With Horizontal Auto Swing | |
| - With Filter Clean Indicator | |
| - With Self Diagnostic | |
| - With Precise Temperature Control | |
| - With Voltage Range | |
| - With Remote Control | |
| - Atleast LxWxH: 80cm x 66cm x 42.8cm | |
| | |

| | | Comply/Not Comply |
|----------------------------------|---|--------------------------|
| Capacity | 2.5Hp | |
| Type | Wall-mounted, Split-type, Inverter | |
| Refrigerant | R32 | |
| Rated Cooling Capacity (Min-Max) | At least 22500 (6600-24500) Btu/h 6.59 (1.93-7.18) kW | |
| Energy Class | 6.0 | |
| Power Consumption (kW) | 1.835 | |
| COP (W/W) | 3.59 | |
| CSPF (Wh/Wh) | 6.10 | |
| Rated Running Current (A) | 8.05 | |
| Energy Efficiency Ratio | 9.24 | |
| Power Supply (V/Ph/Hz) | 220/1/60 | |
| Airflow Rate (H/M/L/Q) | 640/560/480/360 | |
| Sound Level (H/M/L/Q) | 43/41/36/30 | |
| Min Circuit Amps (A) | 12.8 | |
| Sound Level (Outdoor Unit) | 52 dBA | |
| Compressor | Hermetically Sealed Rotary Type | |
| Key Features | Timer, Auto Swing, Fast Cooling, Silent Mode, Wireless Remote | |

| | | Comply/Not Comply |
|----------------------------------|------------------------------------|--------------------------|
| Capacity | 2.0Hp | |
| Type | Wall-mounted, Split-type, Inverter | |
| Refrigerant | R32 | |
| Rated Cooling Capacity (Min-Max) | At least 18000 (5200-18500) Btu/h | |
| Energy Class | 5.28 (1.52-5.42) | |
| Power Consumption (kW) | | |
| COP (W/W) | 1.880 | |
| CSPF (Wh/Wh) | 2.81 | |
| Rated Running Current (A) | 5.02 | |
| Energy Efficiency Ratio | 8.25 | |
| Power Supply (V/Ph/Hz) | 9.85 | |
| Airflow Rate (H/M/L/Q) | 220/1/60 | |
| Sound Level (H/M/L/Q) | 430/380/290/260 | |
| Min Circuit Amps (A) | 42/39/33/30 | |
| Sound Level (Outdoor Unit) | 12.6 | |
| Compressor | 52 dBA | |
| Key Features | Hermetically Sealed Rotary Type | |

| | | Comply/Not Comply |
|----------------------------------|------------------------------------|--------------------------|
| Capacity | 1.5Hp | |
| Type | Wall-mounted, Split-type, Inverter | |
| Refrigerant | R32 | |
| Rated Cooling Capacity (Min-Max) | At least 12300 (4100-13000) Btu/h | |
| Energy Class | 3.6 (1.2-3.81) | |
| Power Consumption (kW) | | |
| COP (W/W) | 1.175 | |
| CSPF (Wh/Wh) | 3.07 | |
| Rated Running Current (A) | 4.6 | |
| Energy Efficiency Ratio | 5.28 | |
| Power Supply (V/Ph/Hz) | 9.96 | |
| Airflow Rate (H/M/L/Q) | 220/1/60 | |
| Sound Level (H/M/L/Q) | 400/330/250/200 | |
| Min Circuit Amps (A) | 39/33/26/21 | |
| Sound Level (Outdoor Unit) | 10.6 | |
| Compressor | 48 dBA | |
| Key Features | Hermetically Sealed Rotary Type | |